



Halotron

*Manufactured and Tested to
ANSI/UL Standards*

*Amerex is an ISO-9001:2000
Registered Firm*

**FAA Approved Model Available
(Model B394TS)**

RUGGED

- ★ Dependable Steel Cylinders
- ★ All Metal Valve Construction

ENVIRONMENTALLY ACCEPTABLE

- ★ EPA approved "Clean Agent" for Class A, B and C hazards
- ★ Low GWP (Global Warming Potential)
- ★ Low ODP (Ozone Depletion Potential)
- ★ Short Atmospheric Lifetime

CLEAN

- ★ Leaves no powder residue

USER FRIENDLY

- ★ Maximum visibility during discharge
- ★ No electrical conductivity back to the operator
- ★ No thermal or static shock
- ★ Bar Coded Labels

(Temperature Range -40°F to 120°F)

Note: 5 lb., 11 lb. and 15 ½ lb. extinguishers are U.S. Coast Guard approved with the bracket listed on the U.L. label.

SPECIFICATIONS							HALOTRON I			
VALVES	ALUMINUM				BRASS, CHROME PLATED					
Size & Capacity (lbs.)	1.4	2½	5	5½	11	15½				
Application	Nozzle				Hose & Nozzle					
Model Number	A384T	B385TS	B386T	B394TS	397	398				
UL & ULC Rating	1B:C	2B:C	5B:C	5B:C	1A:10B:C	2A:10B:C				
Shipping Weight (lbs.)	3¼	5¼	9½	10	22½	27½				
Height (in.)	10	15½	15¼	15¼	21½	21½				
Width (in.)	3½	5½	5¼	5¼	9¼	9¼				
Depth (Diam. - in.)	2 7/8	3	4¼	4¼	6	6				
Range (ft.)	6 - 8	6 - 10	9 - 15	9 - 15	9 - 15	12 - 18				
Discharge Time (sec.)	9	9	9	9	9	14				
Available with Chrome Plated Cylinder	Yes	Yes	Yes							
Standard Bracket	Vehicle	Vehicle	Vehicle Marine	Aircraft	Wall	Wall				

Stored Pressure



**FAA Approved
(Model B394TS)**



**397
398**

**A384T
B385TS
B386T
B394TS**

HALOTRON I is a "Clean Agent" HydroChloroFluoroCarbon discharged as a rapidly evaporating liquid which leaves no residue. It effectively extinguishes Class A and B fires by cooling and smothering and it will not conduct electricity back to the operator. Halotron is pressurized with Argon gas and is an EPA and FAA approved HCFC blend B agent approved for use on Class A, B and C fires. It has a *low* GWP of 0.04 - 0.24, *low* ODP of 0.014 (twelve times lower than the EPA maximum allowable ODP of 0.20) and a *low* Atmospheric Lifetime (3½ to 11 years). Halotron is intended for use in areas formerly protected by Halon 1211 hand portable extinguishers such as computer rooms, telecommunications facilities, clean rooms, data storage areas, offices (for protection of sensitive electronic equipment), boats and vehicles.

**AVAILABLE IN WHEELED EXTINGUISHERS
U.L. LISTED - 1 YEAR WARRANTY**