



Halon 1211

Manufactured and Tested to ANSI/UL Standards
 ISO-9001:2000 / ISO-14001:2004 Certified
UL LISTED AND USCG APPROVED*

RUGGED

- ★ Dependable Drawn Steel Cylinders
- ★ All Metal Valve Construction

CLEAN

- ★ Leaves no residue
- ★ Reclaimed Halon 1211 is Restored to Original Military Specification
- ★ Uses All Recycled Gas in Accordance With The Montreal Protocol

USER FRIENDLY

- ★ Maximum Visibility During Discharge
- ★ No Electrical Conductivity Back to the Operator
- ★ No Thermal or Static Shock
- ★ Bar Coded and Bi-lingual Labels

(Temperature Range -65°F to 120°F)

* All extinguishers USCG approved except model A344T

SPECIFICATIONS	HALON 1211		
VALVES	CHROME PLATED BRASS		
Size & Capacity (lbs.)	9	13	17
Application	Hose		
Model Number	B369	B371	361
UL Rating	1A:10B:C	2A:40B:C	4A:80B:C
Shipping Weight (lbs.)	16¼	22	36¼
Height (in.)	16¼	20¼	23 7/8
Width (in.)	8½	8½	9¼
Depth (Diam. - in.)	5	5	7
Range (ft.)	12-18	12-18	12-18
Discharge Time (sec.)	9	14	22
Minimum Space Requirement (cu. ft.)	1123	1622	2120
Standard Bracket	Wall	Wall	Wall

SPECIFICATIONS	HALON 1211			
VALVES	ALUMINUM			
Size & Capacity (lbs.)	1¼	2½	3	5
Application	Nozzle		Hose	
Model Number	A344T	* C352TS	* C354TS	B355T
UL Rating	2B:C	5B:C	5B:C	10B:C
Shipping Weight (lbs.)	2¾	5½	6	9¾
Height (in.)	10	14 3/8	14 3/8	15¼
Width (in.)	3 5/8	4½	6	5¾
Depth (Diam. - in.)	2 5/8	3	3	4¼
Range (ft.)	9-12	9-15	9-15	9-15
Discharge Time (sec.)	10	10	12	10
Minimum Space Requirements (cu. ft.)	156	312	375	624
Standard Bracket	Vehicle	Aircraft	Aircraft	Veh/Marine

* Modified valve

Stored Pressure



Models
 B369
 B371
 361

Models
 A344T
 C352TS
 C354TS
 B355T

HALON 1211 is a liquified gas, pressurized with nitrogen, which discharges as a vapor causing no cold or static shock and no impairment of the operator's vision. This "CLEAN" agent quickly penetrates difficult to see and hard to reach areas and leaves no residue. It is recommended for protection of delicate, sensitive and expensive computers, electrical equipment, tapes and film, automotive and aircraft engines, laboratory chemicals and equipment.

Quality industrial grade hardware, "CLEAN" agent, light weight, good discharge range and excellent fire extinguishing ability.

1 YEAR WARRANTY