



# Purple K Dry Chemical

## Stored Pressure

Manufactured and Tested to  
ANSI/UL Standards  
ISO-9001:2000 / ISO-14001:2004 Certified  
UL LISTED AND USCG APPROVED

- ★ Dependable Drawn Steel Cylinders
- ★ All Metal Valve Construction
- ★ Easy and more economical to maintain and service
- ★ Bar Coded and Bi-lingual Labels



**PURPLE K** extinguishers contain specially fluidized and siliconized potassium bicarbonate dry chemical which is particularly effective on Class B flammable liquids and pressurized gases. It is electrically non-conductive. Purple K has been the choice of oil, gas, chemical and utilities industries as the preferred fire fighting agent.

Available in Wheeled and Stationary extinguishers.

**6 YEAR WARRANTY**

(Temperature Range -65°F to 120°F)

Note: All extinguishers are U.S. Coast Guard approved with bracket listed on U.L. label.

| SPECIFICATIONS                        | PURPLE K Dry Chemical |                 |         |                      |         |
|---------------------------------------|-----------------------|-----------------|---------|----------------------|---------|
|                                       | ALUMINUM              |                 |         | BRASS, CHROME PLATED |         |
| VALVES                                |                       |                 |         |                      |         |
| Size & Capacity (lbs.)                | 2 ½                   | 5               | 20      | 10 Tall              | 20      |
| Application                           | Nozzle                | Hose and Nozzle |         |                      |         |
| Model Number                          | B410T                 | B479<br>B479T   | A413    | B460                 | 415     |
| U/L Rating                            | 10B:C                 | 30B:C           | 120B:C  | 80B:C                | 120B:C  |
| Shipping Wt. (lbs.)                   | 5½                    | 9½              | 38      | 19                   | 39      |
| Height (in.)                          | 15½                   | 15¼             | 23¼     | 20½                  | 24      |
| Width (in.)                           | 5¾                    | 7¼              | 10¼     | 8¾                   | 10¼     |
| Depth (Diam. - in.)                   | 3                     | 4¼              | 7       | 5                    | 7       |
| Range (ft.)                           | 9 - 15                | 12 - 18         | 15 - 21 | 15 - 21              | 15 - 21 |
| Discharge Time (sec.)                 | 10                    | 12              | 28      | 22                   | 28      |
| Available with Chrome Plated Cylinder | Yes                   | Yes             |         | Yes                  |         |
| F. M. Approved                        | Yes                   |                 | Yes     | Yes                  | Yes     |
| Standard Bracket                      | Vehicle - Marine      |                 |         | Wall                 |         |